

**Declaration of Performance**
**CONSTRUCTION PRODUCTS REGULATION 2011  
DECLARATION OF PERFORMANCE**
**No. AL-0000402081**

1. Unique identification code of the product-type:

**Briton 378, 378D, 378.D, 378M, 378OEM**
**Accessories: - 378DDS & 378MDS, Briton 1413/LE & 1413/KE, 1413.LE & 1413.KE & 1413.BP. Briton 9260 Codelock.**
**P816 & 816 Rim Cylinder**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Briton 378, 378D, 378.D, 378M, 378OEM**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors  
Or  
Locked doors on Escape routes**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1125: 2008  
Notified Certification body No.1121 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 1121-CPR-AAA011**

8. European Technical Assessment:

**N/A**

9. Declared performance

Essential characteristics	Performance	Harmonised technical Specification
<b>Clause 4.2.1 Ability to release (for doors on escape routes)</b>		<b>EN 1125:2008</b>
<b>Release function</b>	< 1 sec	
<b>Panic exit device mounting</b>	Pass	
<b>Exposed edges and corners</b>	> 0,5 mm	
<b>Double doorset</b>	Pass	
<b>Bar installation</b>	Z < 150 mm from frame stop	
<b>Bar length</b>	> 60% of max door width	
<b>Bar projection</b>	W < 100 mm	
<b>Bar end</b>	Pass	
<b>Operating bar face</b>	> 18 mm	
<b>Test rod</b>	Pass	


Door face gap	> 25 mm	
Accessible gap	Pass	
Door free movement	Pass	
Top vertical bolt	N/A	
Keepers	Pass	
Keepers dimensions	N/A	
Door mass and dimensions	Door mass ≤ 200 Kg, door height ≤ 2520 mm, door width ≤ 1320 mm	
Outside access device	Pass	
Release forces	< 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N.	
Security requirement	Grade 2	
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes)		
Corrosion resistance	Grade 3: 96 h	
Temperature range	Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C°	
Covers for vertical rods	N/A	
Lubrication	Lubrication every 20 000 cycles	
Re-engagement force	< 50 N	
Durability	Grade 7: 200 000 cycles	
Abuse resistance –Horizontal bar	1 000 N	
Abuse resistance –Vertical rod	N/A	
Final examination	< 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N	
Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes)		
Re-engagement force	< 50 N	
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)		
Durability	Grade 7: 200 000 cycles	
Re-engagement force	< 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)		
Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies	
Control of Dangerous substances	The materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chris Crampton  
Controller - Unitary EMEA, Finance and Accounting



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

28<sup>th</sup> June 2016