
	<h2>DECLARATION OF PERFORMANCE</h2>
	Date of issue: 20/10/2016 Issue No.1
	No. PUKL-CPR-035-2016.10
1	Unique identification of the product-type: Laminated Safety Glass
2	Type and batch numbers: as given on the product label
3	Intended uses: Fire resisting glass
4	Name and contact address of the manufacturer: Promat UK Limited The Sterling Centre Eastern Road Bracknell Berkshire England RG12 2TD www.promat.co.uk
5	Authorised representative: not applicable.
6	System or systems of Assessment and Verification of Constancy of Performance (AVCP): see table in attachment.
7	The construction product is covered by a harmonised standard: EN 14449. Notified product certification body: No. 0336 Certificate of Constancy of Performance (CPR art. 66.2: Manufacturers may draw up a declaration of performance on the basis of a certificate of conformity or a declaration of conformity, which has been issued before 1 July 2013 in accordance with Directive 89/106/EEC):
8	The construction product is not covered by a European Technical Assessment.
9	Declared performance See table in attachment

Signed for and on behalf of the manufacturer by:

Name: Nigel Morrey
 Function: Technical Director, Promat UK Limited



Bracknell, 20th of October 2016

Signature

Table of Declared Performance

Essential characteristics	AVCP systems	6.4mm Laminated Safety Glass	Harmonised technical specification
Resistance to fire	1	NPD	EN 14449
Reaction to fire	3,4	NPD	
External fire performances	3,4	NPD	
Bullet resistance	1	NPD	
Explosion resistance	1	NPD	
Burglar resistance	3	NPD	
Pendulum body impact resistance	3	2B2	
Resistance against sudden temperature change and temperature differentials (K)	4	40	
Wind, snow, permanent and imposed load resistance	4	6	
Direct airborne sound reduction: R_w (C, Ctr)	3	33 (-1; -2)	
Thermal properties: - U-value - Declared emissivity ϵ_d	3	NPD 0.89	
Light transmission/reflection: $\tau_v / \rho_v / \rho'_v$	3	89 / 8 / 8	
Solar energy transmission/reflection: $\tau_e / \rho_e / \rho'_e$	3	77 / 7 / 7	
g-value	3	0.81	
Durability	3	PASS	

NPD: No Performance Determined.